

LOCKABLE INDOOR/OUTDOOR WALL BOX 24 PORTS SC - WP24U1



Browse on Mobile



Browse on Web

NEXCONEC Lockable IP65 & UV Resistant distribution box is supplied unloaded as standard and offers the ability to terminate 24 fibers housed in a strong robust ABS enclosure for indoor and outdoor applications.

An internal detachable tray provides a neat and tidy solution for housing 24 SC simplex connections and splices. The box has 24 patch cord exit points and up to 2 cable entry points which maintain the IP65 rating.

FEATURES

- ✓ UP to 24 splice with SC Simplex Adapter
- ✓ Lockable Door for security
- ✓ IP65 & UV Resistant
- ✓ Accepts loose tube, distribution and pre-terminated cables
- ✓ Removable splice tray for easy installation
- ✓ Integrated bend radius protection
- ✓ ROHS, REACH & SVHC compliant

APPLICATIONS

- ✓ FTTH / FTTx Networks
- ✓ Data communication Networks
- ✓ Indoor/Outdoor Application

SPECIFICATIONS

Parameters	Value
Width	270 mm
Height	340 mm
Depth	110 mm
N° of Port	24 SC Simplex
Max. Splicing Capacity	24 Splices
Cable entry	2
Material	ABS
Net weight (Kg)	1.8
Operating Temperature	-40 °C +60°C
Color	Grey
Compliant to	RoHS, REACH, SVHC

ORDER INFORMATION

Part Number	Product Description
WP24U1	In/Out Lockable Wall Box IP65 UV Resistant 24 Positions SC Simplex Unloaded